podium



PODIUM offers a sleek, low profile power solution for workstations, public and private areas where AC power outlets, USB charging and data/AV connectivity are required.

Constructed from extruded aluminum, with brushed stainless steel faceplate and endplates, PODIUM is also built to last. Combining style and function the "floating" faceplate design not only gives PODIUM a unique and elegant look, but also protects the power sockets from liquid spillage in high risk areas.

Podium is available in 2 and 4 socket versions.

Podium can be specified with TUF HP USB A+C laptop, mobile and tablet charging.





Common Modular Components*











UK unfused























*We stock a variety of other modular components. Please enquire for specifics

Dimensions



Cutout sizes





70mm

podium TECHNICAL

Features

Configuration:

The 2 or 4 PODIUM socket apertures can be configured with any combination of AC power sockets from the OE Elsafe 42mm international range, our class leading TUF-PD USB fast charger, and most types/makes of Data/AV.

Construction:

Socket frame: Brushed stainless steel Body: Aluminium extrusion

End caps: 2mm powder coated mild steel

Colour options:

Brushed stainless steel top plate and black socket fascias.

Testing:

All PODIUM units are manufactured using quality controlled components and practices and are 100% electrically tested before dispatch:

- Visual: Configuration and appearance.
- Power: Continuity, polarity, insulation & earth
- USB charger: Output voltage and resistance
- Data & AV: All sockets continuity tested with batch performance testing.

Soft Wiring (power)

Base entry power cord hardwired to mains AC plug, or hardwired to male Wieland GST connector for "soft wiring" e.g. connection to an under desk module or to mains supply socket via a starter cable.

Podium is designed and intended for commercial use.

248mm

4 gang

R2mm



